



MAST OPTIONS

Lift Height	Type	Available Carriage Width	Stage	Overall Lowered	Overall Extended	Capacity at 24" Load Center	2WD Weight	4WD Weight	Freelift
10' Roller	Notch ITA Class 3	60" 72" 84"	2	100 in	164 in	6500lbs to 10'	12,594 lb	12,934 lb	None
11' Roller	Notch ITA Class 3	48" 60" 72" 84"	3	80 in	166 in	6500lbs to 11'	12,812 lb	13,152 lb	None
15' Roller	Notch ITA - Class 3 or Swing Carriage	60" 72" 84"	2	125 in	212 in	6500lbs to 15'	13,254 lb	13,687 lb	None
20' Freelift	Notch ITA Class 3	60" 72" 84"	3	117 in	277 in	6500lbs to 12' 4500lbs to 15' 2500lbs to 20'	13,972 lb	14,359 lb	80'
22' Roller	Notch ITA or Swing Carriage	60" 72" 84"	3	125 in	300 in	6500lbs to 12' 4500lbs to 15' 2500lbs to 22'	13,874 lb	14,261 lb	None
28' Roller	Notch ITA Class 3	60"	3	146 in	372 in	6500lbs to 12' 4500lbs to 15' 2500lbs to 22' 1000lbs to 28'	14,173 lb	14,457 lb	None

HP6500

PRODUCTIVITY.

HARLO's mid-sized forklift, the HP6500, is the most versatile, offering **six mast height options** and **23 different mast configurations**. The HP6500 is adaptable and can be built to meet a variety of industry specific needs; including the 28' mast assembly preferred in masonry. Its best in class lift capacity paired with HARLO's reputation for long-term dependability, makes the HP6500 the go to rough terrain forklift for many rental yards and is HARLO's bestselling forklift model.

