

830P

PUSH AROUND MAST LIFT

JLG
reachingout®

Performance

Platform Height	8 ft 2 in.	2.5 m
Working Height	14 ft 2 in.	4.32 m
Stowed Height	61.4 in.	1.56 m
Platform Entry Height	14 in.	.36 m
Platform Size (W x L)	28.7 in. x 39.3 in.	.75 x 1.0 m
Overall Vehicle Length	47 in.	1.19 m
Overall Vehicle Width	29.5 in.	.75 m
Gross Vehicle Weight	628 lb	285 kg
Platform Capacity	440 lb	200 kg

Standard Specifications

Power Source

Batteries	12V DC AGM Battery
Battery Charger	Automatic 110V-240V Charger

Standard Features

- Auto-Lok Wheels on Elevation
- Non-Marking Wheels
- Rust-Free Tilt-Up Aluminum Platform
- Protective Wall Bumpers
- Tool Tray
- Frame-Mounted Bubble Level
- Service Prop
- Integrated Fork Pockets
- Detachable Platform Controls with Coil Cable
- Heavy Duty Ultra-Glide Lifting Mast

Accessories & Options

- 110 V or 230V Main Power
- Tilt Alarm with Auto Cut-Out
- Protective Storage Covers



JLG
®

The JLG "1 & 5" Warranty

JLG Industries, Inc. backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable OSHA Regulations in 29 CFR 1910.67, 29 CFR 1926.453, ANSI A92.3-2006, and CSA Standard CSA B354.4, as originally manufactured for intended applications.

Part No.: 3132132
Printed in USA

JLG Industries, Inc.
1 JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

An Oshkosh Corporation Company